



无锡市南方防爆电机有限公司

KBSGZY 系列
矿用隔爆型移动变电站

型号	额定容量 (KVA)	电压组合及分接范围			联结组标号	损耗 (W)		空载 电流 (%)	短路 阻抗 (%)	重量 (Kg)	外形尺寸 (mm) 长*宽*高				
		高压 (kv)	高压分接范围(%)	低压 (KV)		空载	负载								
KBSGZY-50/6	50	6	±5	0.693/0.4	Yy0(d11)	350	550	2.5	4	1950	2990*700*900				
KBSGZY-100/6	100					520	920	2.5	4	2050	3040*720*1000				
KBSGZY-160/6	160					700	1300	2	4	2310	3100*760*1050				
KBSGZY-200/6	200					820	1550	2	4	2550	3150*760*1050				
KBSGZY-250/6	250					950	1800	2	4	3050	3290*780*1100				
KBSGZY-315/6	315					1100	2150	1.8	4	3500	3560*875*1340				
KBSGZY-400/6	400					1300	2600	1.8	4	3750	3565*900*1400				
KBSGZY-500/6	500					1500	3100	1.5	4	4050	3580*950*1485				
KBSGZY-630/6	630					1800	3680	1.5	4	4345	3580*950*1545				
KBSGZY-800/6	800					1.2/0.693	2050	4500	1.0	4	5675	3860*990*1560			
KBSGZY-1000/6	1000			3.45	2350	5400	1.0	4	6600	4000*1060*1615					
KBSGZY-1250/6	1250			1.2	2750	6500	1.0	4	7610	4040*1175*1590					
KBSGZY-1600/6	1600			3.45	3350	8000	0.8	4	9400	4100*1190*1650					
KBSGZY-2000/6	2000				3800	9500	0.6	4.5	9900	4250*1190*1865					
KBSGZY-2500/6	2500			3.45	Yyn0 Dyn11	4500	10600	0.6	5	13750	4550*1200*1900				
KBSGZY-3150/6	3150					5300	12500	0.6	5.5	16750	4800*1250*1800				
KBSGZY-4000/6	4000					6100	14000	0.6	6	19750	4900*1300*1850				
KBSGZY-50/10	50					10	±5	0.693/0.4	YyO(d11)	390	680	2.5	4	2050	3090*720*1000
KBSGZY-100/10	100									560	1050	2.5	4	2400	3240*800*1050
KBSGZY-160/10	160									800	1500	2	4	2800	3390*850*1300
KBSGZY-200/10	200	950	1800							2	4	2950	3390*850*1300		
KBSGZY-250/10	250	1100	2100							2	4	3230	3490*895*1400		
KBSGZY-315/10	315	1300	2500							1.8	4	3600	3620*895*1450		
KBSGZY-400/10	400	1500	3000							1.8	4	3860	3410*910*1500		
KBSGZY-500/10	500	1750	3500	1.5	4					4130	3580*950*1535				
KBSGZY-630/10	630	2000	4100	1.5	4					5480	3990*990*1585				
KBSGZY-800/10	800	1.280.693	2300	5100	1.2					4	6270	4160*1060*1615			
KBSGZY-1000/10	1000	3.45	2600	6100	1.2			4.5	6800	4250*1050*1680					
KBSGZY-1250/10	1250	1.2	3100	7400	1.0			4.5	7750	4330*1175*1790					
KBSGZY-1600/10	1600	3.45	3800	8500	1.0			5	9450	4380*1100*1850					
KBSGZY-2000/10	2000		4500	9700	0.7			5	11850	4590*1200*1900					
KBSGZY-2500/10	2500	3.45	Yyn0 Dyn11	5200	10800			0.7	5.5	14850	5255*1360*1735				
KBSGZY-3150/10	3150			6100	12800			0.7	5.5	18850	5210*1300*1880				
KBSGZY-4000/10	4000			7000	15000			0.7	6	21850	5700*1350*1900				